



Product Information

Mod.R&S 06 | Rev.4 | Update 10/2017 | Page 1



T.T.D. Application Tape

Description Adhesive Polyester Film for the correct application of digital printing materials. It is available in three different grades of adhesion :
ADVANCED, EASY and EVOLUTION.
The adhesive side of the material is protected with silicon paper.



Average thickness
75 microns

Range of application

PRODUCT	TTD ADVANCED (low tack)	TTD EASY (medium tack)	TTD EVOLUTION (high tack)
COLORPRINT	■	■	■
COLORPRINT EXTRA	■	■	■
COLORPRINT NEW M		■	■
COLORPRINT PU / MATT		■	■
COLORPRINT PU EXTRA / MATT		■	■
DIGITAL PERFOR		■	■
HI-5 PRINT MATT		■	■
SOFT PRINT COLOR VIVID / MATT		■	
SUBLITHIN MATT LT		■	■

Procedure Remove the protective paper from T.T.D.
Apply the T.T.D. onto the printed logo, manually or using a laminator, avoiding air bubbles
Remove the backing of the digital, printed media
Heat apply following the instructions of the digital media
Remove T.T.D. Advanced according the given instructions for the product in use..

The product is REACH approved.

N.B. All information here contained are based on our experience.
We recommend to perform a test before starting standard production.
For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C



The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance).
This document can be subject to variations.
Updated versions are available on our website www.siser.com
For further information, please contact our Sales Office.
Thank you

Vragen? Bezoek onze website voor meer informatie: www.Design92.com